

## KombiSIGN 71 / LED Permanent Beacon 644 LED Perm. light element 12VDC WH



|           |              |
|-----------|--------------|
| Part No.: | 644.400.54   |
| Series:   | KombiSIGN 71 |



### MECHANICAL DATA

|                             |        |
|-----------------------------|--------|
| Height                      | 66 mm  |
| Diameter                    | 70 mm  |
| Materials                   | PC     |
| Dome colour                 | Clear  |
| Protection category         | IP65   |
| Working temperature minimum | -20°C  |
| Working temperature maximum | +50°C  |
| Weight with packaging       | 73 g   |
| Product weight              | 54.4 g |

### ELECTRICAL DATA

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 12V                |
| Operating voltage type      | DC                 |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 12 VDC             |
| Rated operational current   | 50 mA              |
| Protection class            | Protection class 2 |
| Pollution degree            | 3                  |

### OPTICAL DATA

|                      |                  |
|----------------------|------------------|
| Light source         | LED              |
| Light colour         | White            |
| Optical signal image | Permanent        |
| Service life optical | 50,000 h minimum |

### APPROVAL DATA

|                               |                       |
|-------------------------------|-----------------------|
| Conforms with CE              | Yes                   |
| Conforms with RoHS directive  | Yes                   |
| WEEE                          | Yes                   |
| Conforms with ATEX-directive  | No                    |
| Conforms with CCC-Ex          | No                    |
| Conforms with CCC             | No                    |
| Conforms with UL              | cULus                 |
| UL Type Rating                | Type 12               |
| Conforms with FCC             | No                    |
| Conforms with IC              | No                    |
| EAC certificate available     | Yes                   |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with CMIM            | No                    |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / LED Permanent Beacon 644

## LED Perm. light element 12VDC WH

|                       |    |
|-----------------------|----|
| Conforms with AS-I    | No |
| Conforms with DNV     | No |
| Conforms with RoHS CN | No |
| Conforms with VdS     | No |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.