

## KombiSIGN 70 / Permanent Beacon 840

# Perm. light element 12-230VAC/DC BU



$\epsilon$

MECHANICAL DATA		
Height	66 mm	
Diameter	70 mm	
Materials	PC	
Dome colour	Blue	
Protection category	IP54	
Working temperature minimum	-20°C	
Working temperature maximum	+50°C	
Weight with packaging	82 g	
Product weight	67 g	

ELECTRICAL DATA		
Operating voltage	12-230V	
Operating voltage type	AC/DC	
Protection class	Protection class 2	
Pollution degree	3	
Overvoltage category	II	
Isolation voltage	Ui = 250V; Uimp = 2.500V	
Power illuminant	max.5W	

OPTICAL DATA	
Light source	Filament lamp
Light colour	Blue
Service life optical	depends on bulb
Lamp fitting/socket	B15d

APPROVAL DATA	
Conforms with CE	Yes
Conforms with RoHS directive	Yes
WEEE	Yes
Conforms with ATEX-directive	No
Conforms with CCC	No
Conforms with UL	cULus
UL Type Rating	Type 12
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	Yes
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)
Conforms with CMIM	No
Conforms with AS-I	No

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



### KombiSIGN 70 / Permanent Beacon 840

# Perm. light element 12-230VAC/DC BU

ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No

# \$\frac{2\cdot \cdot \cdo

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.