Modular Signal Towers / KombiSIGN 71 LED Perm. light multicolour 24VDC MC



ļ

Part No.:	644.450.55	
Series:	KombiSIGN 71	
MECHANI	CAL DATA	
Height		66 mm
Diameter		70 mm
Materials		PC
Dome colour		Clear
Protection category		IP65
Working temperature minimum		-20°C
Working temperature maximum		+50°C
Weight with packaging		81 g
Product weight		67 g
ELECTRIC	AL DATA	
Operating voltage		24V
Operating voltage type		DC
Operating voltage tolerance		+/- 10%
Rated operational voltage		24 VDC
Rated operational current		120 mA
Rated inrush current		500 mA
Protection class		Protection class 2
Pollution degree		3
OPTICAL I	DATA	
Light source		LED
Light colour		MC 7 colours
Optical signal image		Permanent
Service life optical		50,000 h maximum
APPROVA	L DATA	
Conforms with CE		Yes
Conforms with RoHS directive		Yes
WEEE		Yes
Conforms with ATEX-directive		No
Conforms w	vith CCC	No
Conforms with UL		cULus
UL Type Rating		Type 12
Conforms v	vith FCC	No
Conforms v	vith IC	No
EAC certificate available		Yes
Conforms with UKCA (Importer)		Yes (WERMA (UK) Ltd.)
Conforms with CMIM		No

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Modular Signal Towers / KombiSIGN 71 LED Perm. light multicolour 24VDC MC

Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No

Provide the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.