

Completely pre-assembled Signal Towers / KOMPAKT 37
K37cl sr cable EM 24VAC/DC BU/GN/YE/RD



| | |
|-----------|------------|
| Part No.: | 698.350.75 |
| Series: | Kompakt 37 |



MECHANICAL DATA

| | |
|------------------------------|-----------------------------|
| Height | 209 mm |
| Diameter | 38 mm |
| Materials | PC |
| Dome colour | Clear |
| Housing colour | Silver |
| Protection category | IP65 |
| Connection | Cable |
| cross-sectional area maximum | 0,34mm ² / 22AWG |
| Cable entry | Membrane grommet |
| Cable entry minimum | d = 1 mm |
| Cable entry maximum | d = 9 mm |
| Cable length | 2000 mm |
| Tension relief | Pull-out protection |
| Type of fixing | Built-in mounting |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 231 g |
| Product weight | 190 g |

ELECTRICAL DATA

| | |
|-----------------------------|---------------------------|
| Operating voltage | 24V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 135 mA |
| Rated inrush current | 500 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |
| | In the connection area: 2 |

OPTICAL DATA

| | |
|----------------------|--------------------------------|
| Light source | LED |
| Light colour | Blue Green Red Yellow |
| Optical signal image | Permanent |
| Service life optical | 50,000 h maximum |



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / KOMPAKT 37 K37cl sr cable EM 24VAC/DC BU/GN/YE/RD

| APPROVAL DATA | |
|-------------------------------|-----------------------|
| Conforms with CE | Yes |
| Conforms with RoHS directive | Yes |
| WEEE | Yes |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 Type 4X |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | Yes |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

K37cl sr cable EM 24VAC/DC BU/GN/YE/RD

Technical drawing showing the dimensions of the 698/699 series heat exchangers. The drawing includes side and front views of five different sizes of the unit. The dimensions are as follows:

- Top diameter: $\varnothing 37,5$
- Tube pitch (vertical spacing): 34
- Tube length (horizontal spacing): 12,8
- Mounting bracket height: 8,5
- Mounting bracket diameter: $\varnothing 27,7$
- Mounting bracket thread: M22x1,5
- Overall heights (from bottom to top): 46,7, 127,5, 161,5, 195,5, 229,5

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.