

Completely pre-assembled Signal Towers / KOMPAKT 37 K37cl sr cable EM 24VAC/DC BU/WH/GN/YE/R



Part No.:	698.360.75
Series:	Kompakt 37



MECHANICAL DATA

Height	243 mm
Diameter	38 mm
Materials	PC
Dome colour	Clear
Housing colour	Silver
Protection category	IP65
Connection	Cable
cross-sectional area maximum	0,34mm ² / 22AWG
Cable entry	Membrane grommet
Cable entry minimum	d = 1 mm
Cable entry maximum	d = 9 mm
Cable length	2000 mm
Tension relief	Pull-out protection
Type of fixing	Built-in mounting
Working temperature minimum	-20°C
Working temperature maximum	+50°C
Weight with packaging	243 g
Product weight	205 g

ELECTRICAL DATA

Operating voltage	24V
Operating voltage type	AC/DC
Operating voltage frequency	50Hz
Operating voltage tolerance	+/- 10%
Rated operational voltage	24 VDC
Rated operational current	175 mA
Rated inrush current	500 mA
Protection class	Protection class 2
Pollution degree	3
	In the connection area: 2

OPTICAL DATA

Light source	LED
Light colour	Blue Green Red White Yellow
Optical signal image	Permanent
Service life optical	50,000 h maximum



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / KOMPAKT 37 K37cl sr cable EM 24VAC/DC BU/WH/GN/YE/R

APPROVAL DATA	
Conforms with CE	Yes
Conforms with RoHS directive	Yes
WEEE	Yes
Conforms with ATEX-directive	No
Conforms with CCC	No
Conforms with UL	cULus
UL Type Rating	Type 12 Type 4X
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	Yes
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)
Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

K37cl sr cable EM 24VAC/DC BU/WH/GN/YE/R

The technical drawing illustrates five variations of the 698/699 series LED strip light profile, differing in their total height. Each profile features a black outer casing with horizontal ridges and a white base section. Internal components, including LEDs and electronic drivers, are visible through cutaway sections. The profiles are designed for surface or recessed installation, as indicated by the mounting holes at the bottom.

Profile Height	Width (Ø)	Mounting Hole Diameter (Ø)	Mounting Hole Pitch (mm)
127.5 mm	37.5 mm	27.7 mm	8.5 mm
161.5 mm	37.5 mm	27.7 mm	8.5 mm
195.5 mm	37.5 mm	27.7 mm	8.5 mm
209.5 mm	37.5 mm	27.7 mm	8.5 mm
229.5 mm	37.5 mm	27.7 mm	8.5 mm

3/3