## Completely pre-assembled Signal Towers / eSIGN eSIGN 15 Segments WH



ļ

Part No.:	657.700.55		
Series:	eSIGN		
MECHANICAL DATA			
Height		372 mm	
Diameter		72 mm	
Materials		PC	
Dome colour		Tranclucent	
Housing colour		White	
Protection category		IP66 IP69K	
Connection		M12 plug 8-pole	
Type of fixing		Base mounting Tube mounting	
Working temperature minimum		-30°C	
Working temperature maximum		+60°C	
Weight with packaging		850 g	
Product weight		794 g	
IK-Code (IEC 62262)		IK08	
ELECTRICAL DATA			
Operating voltage		24V	
Operating voltage type		DC	
Operating voltage tolerance		+/- 10%	
Rated operational voltage		24 VDC	
Rated operational current		555 mA	
Rated inrush current		800 mA	
Protection class		Protection class 3	
Pollution degree		3	
Overvoltage category		l	
Isolation voltage		Ui = 50V / Uimp = 330V	
Request to external PSU		SELV/PELV	
connectivity		Digital entrance USB	
OPTICAL DATA			
Light source		LED	
Light colour		MC >1.000.000 colours	
Optical signal image		Blink Double flash Flash Permanent	
Blink frequency		Configurable	
Service life optical		50,000 h maximum	

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.


## Completely pre-assembled Signal Towers / eSIGN eSIGN 15 Segments WH

APPROVAL DATA			
Conforms with CE	Yes		
Conforms with RoHS directive	Yes		
WEEE	Yes		
Conforms with ATEX-directive	No		
Conforms with CCC-Ex	No		
Conforms with CCC	No		
Conforms with UL	cULus		
UL Type Rating	Type 4/4X/12/13		
Conforms with FCC	No		
Conforms with IC	No		
EAC certificate available	No		
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)		
Conforms with CMIM	No		
Conforms with AS-I	No		
Conforms with DNV	No		
Conforms with RoHS CN	No		
Conforms with VdS	No		
MTTF-value [years]	33		

Provide the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

ļ

Completely pre-assembled Signal Towers / eSIGN eSIGN 15 Segments WH



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.