Certificate of Compliance

Certificate Number(s):
UL-US-2145384-5

Report Reference:
E164155-20210929

Issue Date:
2026-03-09

Issued to:

WERMA Signaltechnik GmbH + Co. KG
Duerbheimer Str. 15, Rietheim-Weilheim, 78604, DE

This certificate confirms that representative samples of:
NMTR - Power Circuit and Motor-mounted Apparatus

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 508, Edition 19, Issue Date 2024-10-28

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2025 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2145384-5
Report reference: E164155-20210929
Issue Date: 2026-03-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Close type Signal Towers High

Model(s): 240 *followed by blanc, followed by 6, followed by 0, followed by 0 to 9, followed by blanc, followed by 09 to 12.*

Close type Signal Towers RGY or RGB

Model(s): 240 *followed by blanc, followed by 3 or 4, followed by 2 or 4, followed by 0 to 9, followed by blanc, followed by 50 or 55.*

Close type Signal Towers Smart

Model(s): 240 *followed by blanc, followed by 5, followed by 2, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Model(s): 240 *followed by blanc, followed by 6, followed by 2, followed by 0 to 9, followed by blanc, followed by 02 to 03.*

Close type Signal Towers with IO-Link

Model(s): 240 *followed by blanc, followed by 5, followed by 1, followed by 0 to 9, followed by blanc, followed by 00 to 03.*

Close type Signal Towers with IO-Link tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 1, followed by 0 to 9, followed by blanc, followed by 02 to 03.*

Close type Signal Towers with touch function

Model(s): 240 *followed by blanc, followed by 1 or 2, followed by 6, 7, 8 or 9, followed by 0 to 9, followed by blanc, followed by 55.*

Open type Signal Towers High tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 0, followed by 0 to 9, followed by blanc, followed by 01 to 04*

Open type Signal Towers RGY or RGB tube mount

Model(s): 240 *followed by blanc, followed by 5, followed by 0, followed by 0 to 9, followed by blanc, followed by 00 to 03.*

Open type Signal Towers Smart tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 2, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Open type Signal Towers with IO-Link tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 1, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2026 UL LLC. All rights reserved.

Certificate of Compliance

Certificate Number(s):

UL-CA-2138119-5

Report Reference:

E164155-20210929

Issue Date:

2026-03-09

Issued to:

WERMA Signaltechnik GmbH + Co. KG
Duerbheimer Str. 15, Rietheim-Weilheim, 78604, DE

This certificate confirms that representative samples of:

NMTR7 - Power Circuit and Motor-mounted Apparatus Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

CSA C22.2 No. 14, Edition 13, Issue Date 2018-03, Revision Date 2022-06

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch
UL Mark Certification Program Manager

UL Solutions

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2025 UL LLC. All rights reserved.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2138119-5
Report reference: E164155-20210929
Issue Date: 2026-03-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Close type Signal Towers High

Model(s): 240 *followed by blanc, followed by 6, followed by 0, followed by 0 to 9, followed by blanc, followed by 09 to 12.*

Close type Signal Towers RGY or RGB

Model(s): 240 *followed by blanc, followed by 3 or 4, followed by 2 or 4, followed by 0 to 9, followed by blanc, followed by 50 or 55.*

Close type Signal Towers Smart

Model(s): 240 *followed by blanc, followed by 5, followed by 2, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Model(s): 240 *followed by blanc, followed by 6, followed by 2, followed by 0 to 9, followed by blanc, followed by 02 to 03.*

Close type Signal Towers with IO-Link

Model(s): 240 *followed by blanc, followed by 5, followed by 1, followed by 0 to 9, followed by blanc, followed by 00 to 03.*

Close type Signal Towers with IO-Link tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 1, followed by 0 to 9, followed by blanc, followed by 02 to 03.*

Close type Signal Towers with touch function

Model(s): 240 *followed by blanc, followed by 1 or 2, followed by 6, 7, 8 or 9, followed by 0 to 9, followed by blanc, followed by 55.*

Open type Signal Towers High tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 0, followed by 0 to 9, followed by blanc, followed by 01 to 04*

Open type Signal Towers RGY or RGB tube mount

Model(s): 240 *followed by blanc, followed by 5, followed by 0, followed by 0 to 9, followed by blanc, followed by 00 to 03.*

Open type Signal Towers Smart tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 2, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Open type Signal Towers with IO-Link tube mount

Model(s): 240 *followed by blanc, followed by 6, followed by 1, followed by 0 to 9, followed by blanc, followed by 00 to 01.*

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2026 UL LLC. All rights reserved.